2012 ANNUAL ANALYSIS OF CEDAR & TOLT WATER SUPPLIES

Distribution Water Quality (unless otherwise noted)
Samples Collected: June 19, 2012 (unless otherwise noted)

Cedar Distribution = South of the ship canal & lower elevations North of ship canal.

Tolt Distribution = Higher elevations North of the ship canal.

	State Dept. of Health		i = riigilei elevations North	Minimum
Water Quality Parameter	·	CEDAD	TOLT	
	Maximum Contaminant Level	CEDAR	TOLT	Reporting
Primary Standards *	MCL			Level
Antimony	6 μg/L	ND	ND	0.8
Arsenic	10 μg/L	ND	ND	0.5
Asbestos \$	7 million fibers/L (>10um long)	ND (2009)	ND (2009)	0.2
Barium	2000 μg/L	1.8	1.9	0.2
Beryllium	4 μg/L	ND	ND	0.2
Bromate #	10 μg/L	ND (6/06/12)	ND(7/10/12)	5.0
Cadmium	5 μg/L	ND	0.35	0.2
Chromium	100 µg/L	ND	ND	0.5
Cyanide	200 μg/L	ND	ND	10
Fluoride	4 mg/L	0.77	0.94	0.10
Haloacetic Acids(5), Total~	60 μg/L	34	27	1.0
Mercury	2 μg/L	ND	ND	0.2
Nickel	100 μg/L	ND	ND	0.5
Nitrate-Nitrogen	10 mg/L	0.016	0.129	0.01
Nitrite-Nitrogen	1 mg/L			
	ü	ND	ND	0.002
Selenium	50 μg/L	ND	ND	0.8
Thallium	2 μg/L	ND	ND	0.2
Trihalomethanes, Total~	80 μg/L	37	31	0.5
Turbidity #	5 NTU for Cedar/ 0.30 NTU for Tolt	0.20	0.13	0.05
Secondary Standards **	SMCL			
Aluminum	50 - 200 μg/L	9.5	32	1.0
Chloride	250 mg/L	3.1	2.6	0.5
Color	15 std. units	ND	ND	5
Fluoride	2 mg/L	0.77	0.94	0.10
Iron	300 µg/L	25	30	6
Manganese	50 μg/L	1.4	1.0	0.5
pH, range ++	6.5 - 8.5 pH units, Target 8.2	7.71 - 8.35	8.19 - 8.51	NA
Silver	100 μg/L	ND	0.19 - 0.51 ND	0.8
Solids,Total Dissolved	500 mg/L	36.5	37.3	5.0
Specific Conductance	700 µmhos/cm			
Sulfate	250 mg/L	52.6	55.4	5.0
		9.0	7.4	1.0
Zinc	5000 μg/L	ND	ND	0.8
Other Parameters	Units			
Alkalinity, Total	mg/L (as CaCO ₃)	16.7	17.7	2.0
Bromide	μg/L	ND	ND	5
Calcium	mg/L (as CaCO ₃)	18.8	23.4	2.0
Copper, Source water	μg/L	ND	ND	0.5
Hardness, Total	mg/L (as CaCO ₃)	21.6	25.0	2.0
Hardness, Total	grains/gal. (as CaCO ₃)	1.2	1.4	0.1
Lead, Source water	μg/L	ND	ND	0.5
Magnesium	mg/L	0.82	0.36	0.01
Oxygen, Dissolved	mg/L	12.4	18.4	0.5
Phosphate, soluable-reactive	μg/L	3	2	1
Potassium	mg/L	0.21	0.10	0.02
Silica, Reactive	mg/L	8.6	5.2	1.0
Sodium	mg/L		+	
	-	1.54	0.79	0.08
Temperature, normal annual range	deg. C.	5.4 - 21.8	3.8 - 20.6	NA 0.00
Total Organic Carbon #	mg/L	1.07	0.92	0.20
Residential Survey @	Action Level	Combined System		
2010 Lead Reduced Monitoring	15 μg/L	5.1		1.0
2010 Copper				
Reduced Monitoring	1300 μg/L	135		1.0

Primary and Secondary Standards were measured at the Intake to the distribution system after treatment.

ND = Not Detected at or above the Minimum Reporting Level

^{*} Health stds.: Supplier subject to public notification.

^{**} Aesthetic stds.: Supplier not subject to public notification.

[~] Average of the last 4 quarters testing, through 6/12.

⁺⁺ January-July 2012, 10-90th percentile

^{\$} Test results 9/2/2009.

[#] As measured at treatment plant.

¹ ppm = 1 mg/L = 1000 μ g/L

[@] Measured at 90th percentile of overnight standing residential samples from homes with copper pipes and lead solder. Next round 9/2013.